


SW-30 EXIT VERIFIER



The Exit Verifier:

- Calculates and displays parking fees.
- Processes traditional credit & debit card payments.
- Prints patron receipts upon request.
- Supports LPR imaging.
- Controls barrier gates, electronic signage and more.

Additionally, the SW-30 Exit Verifier accepts and process paid, unpaid or expired tickets, plus validation stickers, vouchers or chaser tickets. The device supports traditional or EMV Chip & Pin bank card processing, proximity access cards, plus Mag-Stripe or Mifare hotel room keys.

TIBA's SW-30 also features a slide-out front panel for receipt paper refills and routine maintenance, storage for thousands of used tickets, plus a built-in audio annunciator and intercom substation.

APPLICATIONS & USES



Mixed usage facilities



Hotel, Valet, event operations



Municipal properties



Residential, commercial complexes



Airports, other transport facilities



Sport arenas, convention centers



Shopping malls



University, medical campuses

FEATURES*

- · Motorized barcode ticket reader
- EMV Chip & Pin
- PCI 3.2 compliant
- 4.3" color TFT customer display
- Mag-Stripe insertion card reader
- RFID proximity card reader
- · Thermal receipt printer
- QR barcode scanner
- Built-in audio annunicator
- · Analog, digital, VoIP intercom options
- · Supports LPR imaging
- Data line surge protection
- · Single lane loop detector
- Thermostat controlled heater
- Stainless steel construction
- Custom panels & housing colors
- ADA compliant
- · CE, FCC, CE, UL certified

^{*} Not all features are available or standard in all regions. Check with your local TIBA representative for availability.

FEATURES

Ticket Reader Motorized barcode ticket verifier

Credit Card Reader Traditional Mag-Stripe or EMV Chip & Pin

QR barcode Scanner eValidations, state driver licenses Receipt Printer For receipts and lost tickets Hotel Keys Mag-Stripe or Mifare room keys Customer Display Hi-resolution TFT color display Analog, digital, VoIP station options Intercom

Built-in Surge Protection

OPERATIONS

Embedded industrial controller Processor

Communication & Network RS-485 industrial communication

or TCP/IP (requires adapter)

Built-In Clock Backed up by lithium ion battery;

Keeps clock and data up to 10 years

Off-Line Operation Full off-line operation supported

Remote Monitoring Real-time transaction & events monitoring

by SmartPark FMS software

HOUSING

Construction Stainless steel

14.0" (35.6 cm) width; 18.7" (47.6 cm) depth; Measurements

49.5" (125.0 cm) height

Weight 127 Lbs. (57 kg)

Standard: White RAL 9010 Color (Housing)

Custom colors available

Locks Two mechanical locks

ELECTRICAL

100 - 240 VAC 50-60 HZ Voltage Current 1A, 5.3A with heater Power Consumption 240W, 640W with heater

Operating Voltage 24VDC

ENVIRONMENTAL CONDITIONS

 -4° to 122° F (-20° to 50°C) with heater Operating Temperature

Water Rating IP54


REGULATORY













Safety • UL 60950-1:2007


EMC • CE, FCC Part 15, Subpart B, Class B













www.tibaparking.com

USA

2228 Citygate Drive, Columbus, Ohio 43219 T. +1 614 328 2040 • F. +1 614 864 2153

ISREAL

17 Ha-Mefalsim Street, Petah-Tikva 4951251 T. +972 3619 9777 • F. +972 3 905 4306