

SW-60 EXIT STATION



- In-lane ticket processing & pay station designed for highthroughput unattended parking operations
- Supports ticketless exit via phone number, credit card, proximity card, barcode credential, and Bluetooth
- · Calculates and displays parking fees
- High-resolution 10.1" color touch screen supports: ticketless, rate display, prepay options, and help services
- Prints patron receipt on demand
- Embedded Voice Over IP intercom and Pinhole IP camera



- Numerous credit card solutions including: Mag-Stripe, P2PE EMV with or without pin pad, and NFC
- Various access credentials include: LPR, HID Proximity, Mifare, Mag-Stripe Room Key, QR barcodes, BLE, AVI, and drivers license
- Supports validation barcode stickers and coupons, reservations, and vouchers
- · Controls barrier gates, electronic signage, lane counts, and more
- Surge protection built in



CREDIBLE

- Rugged, tamper-resistant stainless steel housing
- O/S less embedded technology
- FCC, CE, UL, CSA certified
- PCI 3.2 compliant
- ADA compliant



About the New TIBA X60 Series.

- **Smarter and faster than ever with new product architecture.**
- Increased security to protect your data.
- Connectivity using native TCP/IP and RS485.
- User engagement through extra-large, high contrast touch screen.
- Easy to install, service, and maintain.
- Backward compatibility. Seamlessly mix X30 and X60 devices.
- New technology. More features at a lower cost of ownership.

SW-60 EXIT STATION

FEATURES

Driver Instruction Display 10.1" high-resolution color touch screen display

Ticket Verifier Barcode scanning or motorized barcode ticket reader

Card Holder Access Bluetooth, Proximity, Mifare, AVI, barcode

LPR Imaging Supported

Reads multiple barcode formats - 1D & 2D, QR, PDF417, and **Barcode Scanner**


more. Supports various barcode credentials via mobile

device or paper

Receipt Printer For receipts and lost tickets

Data Line Surge Protection Built-in Heater and Thermostat Supported Hotel Room Keys Supported Built-in Pin Hole Camera Built-in VoIP Intercom

Credit Card Payments Mag-Stripe, P2PE EMV with or without pin pad, NFC



OPERATIONS

Processor High-speed embedded industrial processor

Operating System O/S Less


Communication and Network Native TCP/IP Ethernet, or RS-485 Communication

Built-In Clock Lithium-ion battery

Off-Line Operation Off-line functionality supported

Real-time transaction and events monitoring via Facility Remote Monitoring

Management System



HOUSING

Construction Stainless steel


Measurements 14.9" (37.8 cm) W; 13.1" (33.27 cm) D; 49.9" (126.7 cm) H

Weight Dependent on components selected

Standard: White RAL 9010 Color (Housing)

Faceplate High-grade epoxy-based TIBA standard or custom design

Locks Keyed device lock



ELECTRICAL

Voltage 100-240 VAC, 50-60 HZ

Current 6.5A approximate max. (with heater)

Power Consumption 650W (with heater)

ENVIRONMENTAL CONDITIONS

Operating Temperature -4° to 122°F (-20° to 50°C) with heater

IP Rating 54

REGULATORY

Safety UL 60950-1:2007

CAN/CSA-C22.2 No. 60950-1-07

CE, FCC Part 15, Subpart B, Class B **EMC**



USA 2228 Citygate Drive Columbus, Ohio 43219

17 Hamefalsim Street

ISRAEL

Petah-Tikva, Israel 4951251