

# DECLARATION OF PERFORMANCE (DOP) - BIRCH PLYWOOD

REFERENCE: NTL-2412-CPR-1040-01 IN COMPLIANCE WITH EU REGULATION 305/2011/EU

#### PRODUCT DESCRIPTION

Wood-based panels for use in construction. Non-structural components in internal or external applications in construction, fire impregnated according to the requirements of EN 13986:2004. For further details of delivered product, please see notes per order or visit varmawood.com.

## **MANUFACTURER**

Varmawood Oy - Harjuviidantie 1, 15550 Lahti, Finland

Business ID: 3253143-9

e-mail: info@varmawood.com

#### NOTIFIED CERTIFICATION BODY & AVCP SYSTEM

Control Union Finland Oy (Finotrol), Teollisuuskatu 3, FI-50130 Mikkeli, Finland. Notified certification body no: 2412 has performed initial inspection of the manufacturing plant and production control and performs continuous surveillance, assessment, and evaluation of factory production control under system 1 and issued the certificate of conformity of factory production control: NTL- 2412-CPR-1040-01.

### DECLARED PERFORMANCES AFTER FIRE IMPREGNATION

Table below summarizes certified wood-based panels in accordance with EN 13986:2004 with reference to Certificate of Performance 2412-CPR-1040-01.

# **VARMAWOOD FIRE IMPREGNATED BIRCH PLYWOOD**

#### **CLASS - WOOD-BASED PANELS**

REFERENCES: CLASSIFICATION: EN 13501-1:2018 AND EN 13501-1:2020 - TEST: EN 13823 (SBI) AND EN 14135:2004 Substrate of classes A1 or A2-s1,d0 of at least 11 mm thickness and with a density ≥525 kg/m³. Product fixed mechanically to the substrate. Non-ventilated or ventilated air gap. Mounting with horizontal and vertical joints.

| Species       | Nominal density range (kg/m³) |     | Thickness (mm) |     | Reaction to fire |         |  |
|---------------|-------------------------------|-----|----------------|-----|------------------|---------|--|
| Birch plywood |                               | 745 | •              | ≥12 |                  | B-s1,d0 |  |

| Additional information           |  |  |  |  |  |
|----------------------------------|--|--|--|--|--|
| Sound absorption (Hz):           | 250 Hz – 500 Hz: 0,1 / 1000 Hz – 2000 Hz: 0,3 (EN 13986/Table 10)          |  |  |  |  |
| Fire retardant solution:         | Burnblock  |  |  |  |  |
| Formaldehyde:                    | E1   |  |  |  |  |
| Pentachlorphenol:                | < 5 ppm  |  |  |  |  |
| Water vapour permeability g (μ): | NPD  |  |  |  |  |
| EU Reach Regulation:             | Burnblock fire retardant do not contain any kind of chemicals or dangerous |  |  |  |  |
| EU neach negulation:             | substances. Please see specifications: www.burnblock.com                   |  |  |  |  |
| Document version & Date          | 1.0, 2024-10-14  |  |  |  |  |

Manufacturer's signature in Nastola, August 26th 2024

Vincent Parasnis, CEO, Nordic Timber Labs Oy / Varmawood



