

DECLARATION OF PERFORMANCE (DOP) - PINE PLYWOOD

REFERENCE: NTL-2412-CPR-1040-01 IN COMPLIANCE WITH EU REGULATION 305/2011/EU

PRODUCT DESCRIPTION

Wood-based panels for use in construction. Non-structural components in internal or external applications in construction, fire impregnated according to the requirements of EN 13986:2004. For further details of delivered product, please see notes per order or visit varmawood.com.

MANUFACTURER

Varmawood Oy - Harjuviidantie 1, 15550 Lahti, Finland

Business ID: 3253143-9

e-mail: info@varmawood.com

NOTIFIED CERTIFICATION BODY & AVCP SYSTEM

Control Union Finland Oy (Finotrol), Teollisuuskatu 3, FI-50130 Mikkeli, Finland. Notified certification body no: 2412 has performed initial inspection of the manufacturing plant and production control and performs continuous surveillance, assessment, and evaluation of factory production control under system 1 and issued the certificate of conformity of factory production control: NTL- 2412-CPR-1040-01.

DECLARED PERFORMANCES AFTER FIRE IMPREGNATION

Table below summarizes certified wooden panels in accordance with EN 13986:2004 with reference to Certificate of Performance 2412-CPR-1040-01.

VARMAWOOD FIRE IMPREGNATED PINE PLYWOOD

CLASS - WOOD-BASED PANELS

REFERENCES: CLASSIFICATION: EN 13501-1:2018 AND EN 13501-1:2020 - TEST: EN 13823 (SBI) AND EN 14135:2004 Substrate of classes A1 or A2-s1,d0 of at least 11 mm thickness and with a density ≥525 kg/m³. Product fixed mechanically to the substrate. Non-ventilated or ventilated air gap. Mounting with horizontal and vertical joints.

Species	Nominal density range (kg/m³)		Thickness (mm)		Reaction to fire		
Pine plywood		684	F	≥12		B-s1,d0	

Additional information					
Sound absorption (Hz):	250 Hz – 500 Hz: 0,1 / 1000 Hz – 2000 Hz: 0,3 (EN 13986/Table 10)				
Fire retardant solution:	Burnblock				
Formaldehyde:	E1				
Pentachlorphenol:	< 5 ppm				
Water vapour permeability g (μ):	NPD				
EU Reach Regulation:	Burnblock fire retardant do not contain any kind of chemicals or dangerous				
EU neach negulation:	substances. Please see specifications: www.burnblock.com				
Document version & Date	1.0, 2024-10-14				

Manufacturer's signature in Nastola, August 26th 2024

Vincent Parasnis, CEO, Nordic Timber Labs Oy / Varmawood



