1. Parquet nominal dimensions:

Nominal dimensions	*1-strip board*	*3-strip board*	*Herringbone*	*Chevron*
Width,mm	182/165/150	196	150	120
Length, mm	2200,2000,1800,1600	2200	600	600
Length parameter, mm	+/- 0,5	+/- 0,5	+/- 0,5	+/- 0,5
Thickness, mm	14	14	14	14
Wear layer thickness, mm	3,5 +/- 0,15	3,5 +/- 0,15	3,5 +/- 0,15	3,5 +/-0,15

2. Technical requirements for 1 strip parquet board:

The name of the wood defect on the front side	*Grade Comfort*	*Grade Classic*	*Grade Rustic*
Color variation	Slight difference	significant difference	unlimited
Knots:	Healthy knot till 8 mm	Healthy till 30 mm, falling out filled knots till 10 mm	Healthy till 60 mm, falling out filled till 40 mm
Cracks:	Not allowed	Allowed filled	allowed filled
Wormholes	Not allowed	Not allowed	Not allowed
Processing defects	Not allowed	Not allowed	Not allowed

3. Technical characteristics of coating:

Type of coating	*lacquer*
Gloss degree, GU	10 - 15 gloss
scratch resistance test, EN14354	8800 об.
wear resistance, EN13329	>/= 4000
Application area	Residential and public spaces
Warranty for floors, years	With proper operation 20 years