



ТОВ "ГЛОБАЛ ОПТ ТРЕЙД"

Марка насоса	Діаметр робочого коlesa, мм	Подача, м³/год	Напор, м	Частота обертання, об/хв	Допустима вакуумметр. висота всмоктування, м	ККД % не менше	Потужність двигуна, кВт	Марки насосів що заміняються за параметрами (для довідок)
Д 200-36	350	200	36	1450	4,5	74	37	5НДв 5НДВ-60
Д 200-36а	320	190	30			71	30	
Д 200-366	300	180	25			66	22	
Д 200-90-2	260	200	90	2900	4,0	75	90	4НДв 4НДВ-60 Д200-95
Д 200-90а-2	240	180	74			72	75	
Д 200-906-2	225	160	62			69	55	
Д 315-71-2	240	315	71			83	110	
Д 315-71а-2	222	300	64			80	90	
Д 315-71-2	240	150	18	1450	5,0	83	15	6НДС 6НДС-60 Д320-70
Д 320-50	405	320	50			77	75	
Д 320-50а	365	300	41			74	55	
Д 320-506	340	300	30			69	45	
Д 320-90	267	320	90			74	132	
Д 630-90	525	630	90	1450	4,0	75	250	8НДв 8НДВ-60
Д 630-90а	475	575	74			74	200	
Д 630-906	450	500	65			72	160	
Д 630-90	525	500	36			75	110	
Д 630-90а	475	450	32			74	75	
Д 630-906	450	350	27	960	4,5	72	55	1Д 500-63
1Д 630-90	520	630	90			77	250	
1Д 630-90а	470	550	74			74	200	
1Д 630-906	435	500	60			69	160	
1Д 630-90	520	500	38			77	110	
1Д 630-90а	470	470	30	960	4,5	74	75	12НДС 12НДС-60
1Д 630-906	435	420	25			69	55	
Д 1250-65	460	1250	65		3,5	86	315	
Д 1250-65а	430	1000	53			84	250	
Д 1250-656	390	900	45			80	200	
Д 1250-65	460	800	27	960	4,0	86	110	
Д 1250-65а	430	700	24			84	75	
Д 1250-656	390	500	20			80	55	
1Д 1250-63	455	1250	63	1450	3,5	86	315	14Д6
1Д 1250-63а	425	1100	525			83	250	
1Д 1250-636	395	1050	44			78	200	
1Д 1250-63	455	800	28			86	110	
1Д 1250-63а	425	740	24			83	75	
1Д 1250-636	395	710	20	1450	4,0	78	55	14НДС
Д 1250-125	625	1250	125			76	630	
Д 1250-125а	570	1050	102			73	500	
Д 1250-1256	535	915	91			70	400	
1Д 1250-125	615	1250	125			78	630	
1Д 1250-125а	570	1150	102	960	3,0	75	500	14НДС
1Д 1250-1256	530	1030	87			70	400	
1Д 1600-90	540	1600	90			85	630	
1Д 1600-90а	495	1450	75			82	500	
1Д 1600-906	460	1300	63			77	400	
1Д 1600-90	540	1000	40	1450	4,0	85	160	14НДС
1Д 1600-90а	495	970	34			82	132	
1Д 1600-906	458	870	30			77	110	
200Д90	500	720	90			81	250	
200Д90а	475	720	80			80	250	
200Д906	450	700	74	960	5,0	78	200	14НДС
200Д90	500	480	38			81	90	
200 Д90а	475	480	30			80	75	
200 Д906	450	460	25			78	55	
300Д70	460	1080	69	1450	3,5	86	315	14НДС
300Д70а	430	1050	58			85	250	
300Д706	410	1050	48			83	200	
300Д70	460	750	28			86	90	
300Д70а	430	720	25			85	75	
300 Д706	410	720	21	960	4,0	83	55	